

Nitrile General Purpose Gloves



Features and Benefits

- Effective protection against liquids, chemicals, and oils.
- Excellent puncture and abrasion resistance.
- General Purpose version of A11A1.
- Powder Free.
- Ambidextrous.
- Eliminates exposure to latex.
- Textured surface for improved grip.
- Complies with FFDC food handling requirements 21 CFR, Parts 170-199.

Usage



Specifications



Ordering Information

ITEM NUMBER	SIZE	FINGER THICKNESS	PALM THICKNESS	GRAM WEIGHT*	INNER BOX	OUTER CASE
A13A11	SM	3.5 mil +/- 0.5 mil	2.8 mil +/- 0.5 mil	3.5g +/- 0.2g	8-10073-73717-4	8-10073-73718-1
A13A12	MD				8-10073-73720-4	8-10073-73721-1
A13A13	LG				8-10073-73723-5	8-10073-73724-2
A13A14	XL				8-10073-73726-6	8-10073-73727-3
A13A15	XXL				8-10073-73729-7	8-10073-73730-3

*Based on size M

ITEM NUMBER	QUANTITY	INNER BOX DIMENSIONS	CASE DIMENSIONS	TI/HI	CASE WEIGHT (LBS.)	COUNTRY OF ORIGIN
A13A11	100/bx 10 bx/cs	8.8 x 4.9 x 2.2"	11.2 x 10.0 x 9.3"	16/6	8.6	Indonesia Cambodia Vietnam Malaysia Thailand
A13A12					9.5	
A13A13					10.4	
A13A14					11.2	
A13A15	90/bx 10 bx/cs	12.1				

Finding the right hand protection doesn't have to be complicated. Consider VGuard® gloves as an extension of our promise to you: High quality products, great value and excellence in service. If ever you have a question regarding which glove is best for your application, we're here to help. VGuard® is protection you can count on!

Vanguard Safety

Cumming, GA 30041 • 1-866-VGUARD-6 (1-866-848-2736)
 Info@VanguardSafety.com • www.VanguardSafety.com

Nitrile General Purpose Gloves



Composition

Material:	Nitrile synthetic rubber
Allergen content:	Contains no proteins found in latex
Powdered:	No, as per ASTM D6124

Quality

Quality Assurance:	ISO:9001, ISO:14001, GMP, HACCP
Regulatory Compliance:	Complies with FFDC A food handling requirements 21 CFR, Parts 170-199

Technical Data

THICKNESS	MIL
Palm:	2.8 ± 0.5
Finger:	3.5 ± 0.5

Weight*:	3.5 gm ± 0.2
-----------------	--------------

*Based on size M

PHYSICAL PROPERTIES	BEFORE AGING	AFTER AGING
Tensile Strength (MPa):	Min. 14	Min. 14
Ultimate Elongation (%):	Min. 500	Min. 400
Freedom from holes:	AQL 4.0	N/A

DIMENSIONS			
ITEM NO.	SIZE	PALM WIDTH (mm)	LENGTH (mm)
A13A11	Small	80 ± 10	Min. 220
A13A12	Medium	95 ± 10	Min. 230
A13A13	Large	110 ± 10	Min. 230
A13A14	XL	120 ± 10	Min. 230
A13A15	2XL	130 ± 10	Min. 230

COUNTRY OF ORIGIN	HARMONIZATION CODE
Indonesia Cambodia Vietnam Malaysia Thailand	4015.19.1110

Vanguard Safety

Cumming, GA 30041 • 1-866-VGUARD-6 (1-866-848-2736)
 Info@VanguardSafety.com • www.VanguardSafety.com